

What is claimed is:

1. A method of distributing water in an array comprising a plurality of electrochemical fuel cell stacks, wherein said plurality of fuel cell stacks each comprise at least one fuel cell assembly comprising an ion-exchange membrane interposed between a cathode and an anode, said method comprising utilizing water accumulating in an oxidant stream flowing through said plurality of fuel cell stacks by periodically reversing the oxidant stream flow direction within oxidant passages within at least one of said plurality of fuel cell stacks.

2. The method of claim 1 further comprising controlling the temperature profile within said oxidant stream so that oxidant stream temperature generally increases in the flow direction.

3. The method of claim 2 comprising periodically reversing the flow direction of a coolant fluid flowing through each of said plurality of fuel cell stacks.

4. The method of claim 1 further comprising periodically reversing the flow direction of a fuel stream flowing through said plurality of fuel cell stacks to prevent said

12. The method of claim 11 comprising periodically reversing the flow direction of a coolant fluid flowing through said fuel cell.

13. An electrochemical fuel cell assembly comprising an ion-exchange membrane interposed between a cathode and an anode, said assembly further comprising:

5 an oxidant flow field associated with said cathode for directing an oxidant stream to said cathode between a first oxidant flow field port and a second oxidant flow field port;

10 a fuel flow field associated with said anode for directing a fuel stream to said anode between a fuel stream inlet port and a fuel stream outlet port;

15 a coolant system comprising at least one coolant passage associated with said fuel cell for receiving a coolant fluid which flows through said at least one coolant passage;

20 an oxidant stream flow switching device for periodically reversing the direction of flow of said oxidant stream between said first and second oxidant flow field ports; and

25 a coolant fluid flow switching device for periodically reversing the direction of

1000460-0001

flow of said coolant fluid through said at
least one coolant passage.

14. The electrochemical fuel cell assembly
of claim 13 further comprising a controller for
operating said oxidant flow switching device and
said coolant fluid flow switching device such
5 that said oxidant stream flows through said fuel
cell substantially concurrently with said coolant
fluid.

1000450 103401